


Datasheet for: 107928


Tempered coupling DN 6, Exterior thread, Brass, G 1/4 90°

Tempered coupling DN 6, Exterior thread, Brass 2.0401, G 1/4 90°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.36
Article number	107928
EAN/barcode	 4047322258142
Your price	18.86 € / Pcs

Minimum order quantity

Price Unit	1
Quantity Unit	Pcs
Packaging Unit	1
Content	1 St
Minimum order quantity	1

Productdata

Ball	Stainless steel
CAS-No. SVHC 1	7439-92-1
Connecting thread	G 1/4 90°
Length [mm]	47
Material	Brass 2.0401
Max. ambient temperature [°C]	160
Max. medium temperature [°C]	160
Max. operating pressure [bar]	15
Medium	Air, water, oil, vacuum
Min. ambient temperature [°C]	-20
Min. medium temperature [°C]	-20
Page No.	HK615
REACH Info	Contains SVHC ingredient
Retaining ring	Stainless steel
RoHs compliant	yes
SVHC 1	Lead
Sealant	FPM (PTFE coated)
Spring	Stainless steel
a/f [mm]	17
country of origin	DE
customs tariff number	74122000

Variants

<i>Article number</i>	<i>Connecting thread</i>	<i>Price</i>
107928	G 1/4 90°	18.86 € / Pcs
107923	M14x1.5 straight	14.21 € / Pcs
107924	G 1/4 straight	14.21 € / Pcs
107927	M14x1.5 90°	18.86 € / Pcs
107926	G 1/4 45°	18.86 € / Pcs
107925	M14x1.5 45°	18.86 € / Pcs